

Link to the product:
<https://projekt-tech.com/ptbt-eg-lpg-bluetooth-wireless-interface-for-europegas-eg-basico-24-avance-32-48-superior-48-dynamic-p-220.html>



PTBT-EG LPG Bluetooth wireless interface for Europegas EG BASICO 24 AVANCE 32 48 SUPERIOR 48 DYNAMIC

Price	30.00 Euro
Availability	Available
Shipping time	24 hours
Number	PTBT-EG
Manufacturer	Projekt-TECH

Product description

LPG CNG ProjektTECH Bluetooth diagnostic interface in a wireless version with line protection.

A diagnostic device designed for workshop applications. Branded electronics and additional protection systems ensure that our devices operate stably and safely regardless of external factors generated by the running engine and vehicle components (the protection protects transmission lines against the so-called voltage spikes up to 8kV).

3 x LED signaling enables visual assessment of the device's operating status.

The offered interface allows you to perform full diagnostics of the LPG system as well as make adjustments (auto-calibration, maps, switching temperature, rpm, etc.)

It is a fully functional tool enabling full operation of the LPG / CNG system: reading errors, petrol / gas operating parameters, calibration, maps, switching temperatures, revolutions, etc.

FREE PROGRAMS DATABASE

QR code on the casing - bring your phone with the camera on (or a dedicated QR code reading application) close to it to go to the website with free software.

model PTBT-EG interface is fully compatible with ECUs:

- **EuropeGas:** EG BASICO 24, EG AVANCE 32, EG AVANCE 48, EG SUPERIOR 48, EG DYNAMIC

The interface is equipped with an adapter with a splitter:

1. **white rectangular** connector for: **EG Avance and EG Basico**
2. **black oval** connector for operation: **EG Superior**

SOFTWARE (Windows and Linux):

► [free software download site](#)

MAIN FEATURES

- quick installation without the use of additional interface drivers
- supply voltage: 8...16V power consumption: max. 30mA at a voltage of 14.4V
- dimensions (basic interface with electronic): 100x32x15mm / weight: ~0,03kg

- Bluetooth class 2 +EDR (range 10m)
- sensitivity: -84dBm
- operating frequency 2.4GHz
- full 5V voltage on the transmission lines
- connectors adapted to replaceable adapters (adapters from our USB interfaces fit)
- LED signaling in the housing:

IN - transmits the vehicle

OUT - transmits the interface

LINK STATUS - when there is no connection, it flashes / after establishing the connection, it lights up permanently

- the interface electronics (PCB) is machine-made using SMD technology
- housing and label resistant to moisture, insoluble in oils
- made in Poland (EU)

REAL PHOTO





This product has additional options:

Additional adapter EUROPEGAS mol: No.1 & No.10 EG Injecto (Direct Injection) , No.1 & No.10 EG Oscar-N Plus (Mini SAS)/ OBD CAN SAS , No.1 & No.10 Europegas Basico Avance Superior Dynamic